

Time and hours meters electronic

2 presets, PNP, NPN or AC logic

Display LCD, 6-digits, programmable

adparts

BE134



BE134 - two presets

Features

- Hour counter with 2 presets
- Display 6-digits
- Totalizer for hour
- Counting range 9999.99 s / 999.95.9 min / 9999.59 min / 9999.59 h
- With reset
- Connection: Count impulse, NPN, PNP, AC logic
- Batch counter with preset

Technical data - electrical ratings

Voltage supply	22...50 VAC (50/60 Hz) 85...265 VAC (50/60 Hz) 12...30 VDC
Power consumption	5 VA, 5 W
Sensor supply	AC: 24 VDC \pm 20 % / 100 mA DC: 9...28 VDC / 100 mA
Display	LCD, 7-segment display, 2-lines, backlit
Number of digits	6-digits Totalizer in 2 steps (8-digits)
Digit height	7 mm (position value) 4 mm (preset)
Function	Hour counter Main counter with 2 presets
Count mode	Adding or subtracting
Counting frequency	Batch counter: approx. 20 Hz
Presets	1 preset, 2 presets
Operating mode	Time meter and hour counter
Data memory	>10 years in EEPROM
Reset	Button, electric or automatic
Keylock	Yes, electric (keylock)
Outputs electronic	Optocoupler
Outputs relay	Normally open or closed, programmable
Output holding time	0.01...99.99 s
Interface	RS485
Standard DIN EN 61010-1	Protection class II Overvoltage category II Pollution degree 2
Emitted interference	DIN EN 61000-6-4
Interference immunity	DIN EN 61000-6-2
Programmable parameters	Measuring units, sensor logic Control inputs
Approval	UL approval / E63076

Technical data - mechanical design

Ambient temperature	0...+45 °C
Storing temperature	-20...+70 °C
Relative humidity	80 % non-condensing
Connection	Plug-in screw terminal connector
Core cross-section	1.5 mm ²
Protection DIN EN 60529	IP 65 (face with seal)
Operation / keypad	Membrane with softkeys
Housing type	Built-in housing
Dimensions W x H x L	48 x 48 x 100 mm
Installation depth	100 mm
Mounting	Clip frame
Cutout dimensions	45 x 45 mm (+0.6)
Materials	Housing: Makrolon 6485 (PC) Keypad: Polyester
Weight approx.	150 g

